

OMEGA DOUBLE FACE EQUIPMENT



All our vehicular access equipment has a double face version, in which you can blend two machines into one. The faces can be different or the same, choosing between dispenser, reader and payment devices.

Our double face columns allow you to control two independent lanes into a two-way street. Placing this type of equipment in the center of the lane brings an economic saving and makes installation, wiring, use and maintenance easier.

You can make different combinations of barcodes and RFID, making a mix of both. These columns can accept and dispense all kinds of credentials and make payments.

- **V** IP intercom
- **V** For exterior use
- V Barcode/ RFID
- **V** Access by smartphone
- V Dispense, Read and/or Pay
- **V** Customized tickets
- **V** Double face

Customization

Our clients can choose both colors and design of the frontal casing, including advertisements. You can also choose the building material and any color for their exterior finish.



Touch screen

Our columns have two color screens that can be touch screens. This allows you multiple options like selecting different destinations or accessing by a numeric code.



Mifare RFID cards, UHF long range devices, Bluetooth...

Multiple technologies

Our columns have a wide range of readers, 1D or 2D(QR) barcode,

Muelle de rep. de Bouzas A6 36208 Vigo (Spain)



(+34) 986 95 24 47 info@controlsuppliers.com



OMEGA DOUBLE FACE EQUIPMENT

Technical specifications

	Ω Reader Double Face Column	Ω Dispenser- Reader Double Face Column	Columna dispensadora- Vía de pago Doble Cara Ω		
Power	r				
Energy consumption	200-800W				
Power supply	110-240V				
working conditions					
Operability	\rightarrow Cutter life for 1 million cuts \rightarrow 2000 vehicle movements a day				
Temperature	-20°C a 60°C				
Casing					
Dimensions	1315x330x400mm (HxWxD)				
Weight	from 35Kg to 50kg			4	
Material					1330
Steel and acrylic	•				
316 Stainless steel and acrylic	• 0				
Electronic					
Electrónica	ARM Dual Core 1Ghz 1Gb Ram 4Gb Nand Flash				
Operating system	Linux "All RAM"			4	
Communication	Ethernet 10/100 Mbps			4	
Hardware			·		
IP intercom	Microphone and 8Ω speakers				
Screens					
7" TFT high brightness	• –				
7" TFT high brightness touchscreen	0		•		•
Barcode readers					
Insertion	0			-	
Motorized	0		1	* 330 415	-7
2D	0				
Dispenser					
Roll printer			•	1	
Fanfold printer	_	-	_	1	
RFID dispenser	 0		 D	1	
Proximity readers		<u>.</u>			
Mifare		•		1	
Mifare writer	0		1		
125KHz	0		1		
Long range	0		1		
Payment methods		N		Our equipment is integrate	ed into our
Bank card	o •		online platform <i>Control Panel</i> and can be integrated with any other application or platform. It can also work in offline mode if you want it to.		
Pinpad EMW	• •				
Contactless and NFC	 				
Others			I	ii you want it to.	
Heating system		0		From Control Suppliers, we	
Video recorder for users	0			protocols, documentation and support needed to make an easy and quick	
MM detectors	0				
Base configuration Ontional -		-		integration.	

• Base configuration • Optional — Not applicable *Components, materials and designs are subject to future changes without prior notice.

Muelle de rep. de Bouzas A6 36208 Vigo (Spain)



(+34) 986 95 24 47 info@controlsuppliers.com